

For flue gas temperatures above 1600 F, turndowns greater than 3 to 1 will require introduction of flue gas dilution air upstream of the recuperator for its protection. For flue gas temperatures of 1600 F or less, the dilution air may be required when turndown exceeds 6 to 1, depending on the location of the recuperator.


Metric Conversions

1"wc = 25.40 mm H₂O

1 osi = 43.94 mm H₂O = 0.004 39 kg/cm²

C = $\frac{5}{9}$ (F - 32)

1 scfh = 0.028 26 sm³/h = 0.026 86 nm³/h



During periods of system turndown, anytime preheat exceeds 1200 F, either flue gas dilution air must be introduced upstream of the recuperator for its protection, or a portion of the preheated air bled off downstream.

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Parts of this product may exceed 160F in operation and present a contact hazard. Fives North American urges compliance with National Safety Standards and insurance Underwriters recommendations, and care in operation.

Fives North American Combustion, Inc., 4455 East 71st Street, Cleveland, OH 44105 USA, Phone 216.271.6000
Fax 216.641.7852 email: fna.sales@fivesgroup.com • www.fivesgroup.com/fivesna